



TUBULARES CUADRADOS Y RECTANGULARES

Norma : ASTM A500 A ó B
Largos : 12 o 6 metros.

Cuadrados

Dimensión h x b mm	Espesor mm	Peso Kg/m	Sección cm ²	Momento de Inercia cm ⁴		Módulo Resistente cm ³		Radio de Giro cm	
				I _x	I _y	W _x	W _y	i _x	i _y
150 x 150	3	13,92	17,4	622	622	83	83	5,98	5,98
150 x 150	4	18,45	22,9	807	807	108	108	5,93	5,93
150 x 150	5	22,95	28,4	981	981	131	131	5,88	5,88
200 x 200	3	18,63	23,4	1506	1506	151	151	8,02	8,02
200 x 200	4	24,74	30,9	1970	1970	197	197	7,97	7,97
200 x 200	5	30,80	38,4	2410	2410	241	241	7,92	7,92
200 x 200	6	36,81	45,6	2830	2830	283	283	7,88	7,88
250 x 250	4	31,02	39,0	3906	3906	312	312	10,01	10,01
250 x 250	5	38,65	48,4	4800	4800	384	384	9,97	9,97
250 x 250	6	45,20	57,6	5670	5670	453	453	9,92	9,92
300 x 300	4	36,90	47,0	6824	6824	455	455	12,06	12,06
300 x 300	5	45,80	58,4	8414	8414	561	561	12,01	12,01
300 x 300	6	54,70	69,4	9959	9959	664	664	11,96	11,96



Disponibilidad Normal



Venta a Pedido